



SAFETY DATA SHEET (Aerosol) Grey Primer

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	(Aerosol) Grey Primer
SUPPLIER	Autosmart International Ltd Lynn Lane, Shenstone, nr Lichfield Staffordshire. WS14 0DH England www.autosmartinternational.com Tel: +44 (0) 1543 481616 (09:00 - 17:00) Fax: +44 (0) 1543 481549 (09:00 - 17:00) info@autosmartinternational.com
PRODUCT NO.	A42-6
APPLICATION	Primer
EMERGENCY TELEPHONE	Mob: +44 (0) 7808 971321 (24hrs) Tel: +44 (0) 1543 481616 (09:00 - 17:00) Fax: +44 (0) 1543 481549 (09:00 - 17:00)

2 HAZARDS IDENTIFICATION

Extremely flammable. Irritating to eyes. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

CLASSIFICATION (1999/45) Xi;R36. F+;R12. R66, R67.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification (67/548)
2-METHOXY-1-METHYLETHYL ACETATE	203-603-9	108-65-6	5-10%	R10
ACETONE	200-662-2	67-64-1	10-30%	F;R11 Xi;R36 R66 R67
BUTANE	203-448-7	106-97-8	10-30%	F+;R12
BUTANONE	201-159-0	78-93-3	< 1%	F;R11 Xi;R36 R66 R67
BUTYL ACETATE -norm	204-658-1	123-86-4	5-10%	R10 R66 R67
PROPANE	200-827-9	74-98-6	10-30%	F+;R12

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INGESTION

DO NOT INDUCE VOMITING! Rinse mouth thoroughly. Drink plenty of water. Get medical attention if any discomfort continues.

SKIN CONTACT

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

(Aerosol) Grey Primer

EXTINGUISHING MEDIA

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

SPECIAL FIRE FIGHTING PROCEDURES

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours. Be aware of danger of explosion.

UNUSUAL FIRE & EXPLOSION HAZARDS

Aerosol cans may explode in a fire. **HIGHLY FLAMMABLE!**

SPECIFIC HAZARDS

Aerosol containers can explode when heated, due to excessive pressure build-up. Fire creates: Carbon dioxide (CO₂). Carbon monoxide (CO). Nitrous gases (NO_x).

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

For personal protection, see section 8.

ENVIRONMENTAL PRECAUTIONS

Do not discharge into drains, water courses or onto the ground.

SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Read and follow manufacturer's recommendations. During application and drying, solvent vapours will be emitted. Eliminate all sources of ignition.

STORAGE PRECAUTIONS

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. Keep away from heat, sparks and open flame.
 Pressurised container: Must not be exposed to temperatures above 50°C. Store in tightly closed original container in a dry and cool place.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
2-METHOXY-1-METHYLETHYL ACETATE	WEL	50 ppm(Sk)	274 mg/m3(Sk)	100 ppm(Sk)	548 mg/m3(Sk)	
ACETONE	WEL	500 ppm	1210 mg/m3	1500 ppm	3620 mg/m3	
BUTANE	WEL	600 ppm	1450 mg/m3	750 ppm	1810 mg/m3	
BUTANONE	WEL	200 ppm(Sk)	600 mg/m3(Sk)	300 ppm(Sk)	899 mg/m3(Sk)	
BUTYL ACETATE -norm	WEL	150 ppm	724 mg/m3	200 ppm	966 mg/m3	
PROPANE		Asphyxiating	Asphyxiating	Asphyxiating	Asphyxiating	

WEL = Workplace Exposure Limit.

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT



PROCESS CONDITIONS

Provide eyewash station.

ENGINEERING MEASURES

Observe occupational exposure limits and minimize the risk of inhalation of vapours. No specific ventilation requirements noted, except this product must not be used in a confined space without good ventilation.

(Aerosol) Grey Primer

RESPIRATORY EQUIPMENT

If ventilation is insufficient, suitable respiratory protection must be provided. Wear mask supplied with: Gas cartridge suitable for organic substances.

HAND PROTECTION

Use protective gloves made of: Butyl rubber. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

EYE PROTECTION

Not relevant.

OTHER PROTECTION

Wear appropriate clothing to prevent repeated or prolonged skin contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! When using do not eat, drink or smoke. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Aerosol Liquid
COLOUR	Grey
ODOUR	Acetone, ketone.
VOLATILE ORGANIC COMPOUND (VOC)	482

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions and recommended use. Avoid: Heat, sparks, flames. Shocks and physical damage.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

MATERIALS TO AVOID

Strong alkalis. Strong oxidising substances.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂). Nitrous gases (NO_x).

11 TOXICOLOGICAL INFORMATION

GENERAL INFORMATION

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

INHALATION

High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting. Drowsiness, dizziness, disorientation, vertigo.

INGESTION

May cause discomfort if swallowed.

SKIN CONTACT

May cause defatting of the skin, but is not an irritant.

EYE CONTACT

Irritating to eyes.

HEALTH WARNINGS

Because of quantity and composition, the health hazard is small.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

No negative effects on the aquatic environment are known.

13 DISPOSAL CONSIDERATIONS

GENERAL INFORMATION

Do not puncture or incinerate even when empty. Empty aerosols should be recycled where facilities exist. Full or part full aerosols should be disposed of as hazardous waste in accordance with local authority requirements.

DISPOSAL METHODS

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements. Do not allow runoff to sewer, waterway or ground. Recover and reclaim or recycle, if practical.

(Aerosol) Grey Primer**14 TRANSPORT INFORMATION**

UK ROAD CLASS	2.1		
PROPER SHIPPING NAME	AEROSOLS		
UN NO. ROAD	1950	UK ROAD PACK GR.	#
ADR CLASS NO.	2.1	ADR CLASS	Class 2.1: Flammable gases.
ADR PACK GROUP	#	ADR LABEL NO.	2.1
CEFIC TEC(R) NO.	20G5F	RID CLASS NO.	2.1
RID PACK GROUP	#	UN NO. SEA	1950
IMDG CLASS	2.1	IMDG PAGE NO.	93(vol 2)
IMDG PACK GR.	#	EMS	F-D, S-U
MARINE POLLUTANT		UN NO. AIR	1950



AIR CLASS	2.1	AIR PACK GR.	#
-----------	-----	--------------	---

15 REGULATORY INFORMATION

LABELLING



Irritant



Extremely Flammable

RISK PHRASES

R12	Extremely flammable.
R36	Irritating to eyes.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

SAFETY PHRASES

S9	Keep container in a well-ventilated place.
S16	Keep away from sources of ignition - No smoking.
S23	Do not breathe vapour/spray.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S37	Wear suitable gloves.
S38	In case of insufficient ventilation, wear suitable respiratory equipment.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

GUIDANCE NOTES

Workplace Exposure Limits EH40.

16 OTHER INFORMATION

GENERAL INFORMATION

Only trained personnel should use this material.

REVISION DATE 18/03/2010

(Aerosol) Grey Primer

REV. NO./REPL. SDS GENERATED 3

RISK PHRASES IN FULL

R12	Extremely flammable.
R10	Flammable.
R11	Highly flammable.
R36	Irritating to eyes.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.