



## SAFETY DATA SHEET (Aerosol) Mechoil

### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	(Aerosol) Mechoil
PRODUCT NO.	A81
APPLICATION	Universal lubricant
SUPPLIER	Autosmart International Ltd Lynn Lane, Shenstone, nr Lichfield Staffordshire. WS14 0DH England www.autosmartinternational.com Tel: +44 (0) 1543 481616 (09:00 - 17:00) Fax: +44 (0) 1543 481549 (09:00 - 17:00) info@autosmartinternational.com
EMERGENCY TELEPHONE	Mob: +44 (0) 7808 971321 (24hrs) Tel: +44 (0) 1543 481616 (09:00 - 17:00) Fax: +44 (0) 1543 481549 (09:00 - 17:00)

### 2 HAZARDS IDENTIFICATION

Extremely flammable. Repeated exposure may cause skin dryness or cracking.

CLASSIFICATION F+;R12. R66.

### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
BUTANE	203-448-7	106-97-8	10-30%	F+;R12
MINERAL OIL	265-169-7	64742-65-0	5-10%	-
Naphtha (petroleum),hydrotreated heavy	265-150-3	64742-48-9	30-60%	Xn;R65. R10,R66.
PROPANE	200-827-9	74-98-6	10-30%	F+;R12

The Full Text for all R-Phrases are Displayed in Section 16

### 4 FIRST-AID MEASURES

#### INHALATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

#### INGESTION

DO NOT INDUCE VOMITING! Rinse mouth thoroughly. Drink plenty of water. Get medical attention if any discomfort continues.

#### SKIN CONTACT

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

#### EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

### 5 FIRE-FIGHTING MEASURES

#### EXTINGUISHING MEDIA

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

## (Aerosol) Mechoil

### SPECIAL FIRE FIGHTING PROCEDURES

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours. Be aware of danger of explosion.

### UNUSUAL FIRE & EXPLOSION HAZARDS

Aerosol cans may explode in a fire. HIGHLY FLAMMABLE!

### SPECIFIC HAZARDS

Aerosol containers can explode when heated, due to excessive pressure build-up. Fire creates: Carbon dioxide (CO<sub>2</sub>). Carbon monoxide (CO). Nitrous gases (NO<sub>x</sub>).

## 6 ACCIDENTAL RELEASE MEASURES

### PERSONAL PRECAUTIONS

For personal protection, see section 8.

### ENVIRONMENTAL PRECAUTIONS

Do not discharge into drains, water courses or onto the ground.

### SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers.

## 7 HANDLING AND STORAGE

### USAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Read and follow manufacturer's recommendations. During application and drying, solvent vapours will be emitted. Eliminate all sources of ignition.

### STORAGE PRECAUTIONS

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. Keep away from heat, sparks and open flame.  
 Pressurised container: Must not be exposed for temperatures above 50°C. Store in tightly closed original container in a dry and cool place.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
BUTANE	WEL	600 ppm	1450 mg/m <sup>3</sup>	750 ppm	1810 mg/m <sup>3</sup>	
MINERAL OIL	WEL		5 mg/m <sup>3</sup>		10 mg/m <sup>3</sup>	
Naphtha (petroleum),hydrotreated heavy	WEL		1000 mg/m <sup>3</sup>			
PROPANE		Asphyxiating Asphyxiating	Asphyxiating	Asphyxiating Asphyxiating	Asphyxiating	

WEL = Workplace Exposure Limit.

### INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

### PROTECTIVE EQUIPMENT



### PROCESS CONDITIONS

Provide eyewash station.

### ENGINEERING MEASURES

Observe Workplace Exposure Limits and minimise the risk of inhalation of vapours. No specific ventilation requirements noted, except this product must not be used in a confined space without good ventilation.

### RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Workplace Exposure Limit.

### HAND PROTECTION

Use protective gloves made of: Neoprene, nitrile, polyethylene or PVC. or Rubber (natural, latex). Be aware that the liquid may penetrate the gloves. Frequent change is advisable. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Nitrile gloves are recommended.

**(Aerosol) Mechoil****EYE PROTECTION**

Wear approved chemical safety goggles where eye exposure is reasonably probable.

**OTHER PROTECTION**

Wear appropriate clothing to prevent repeated or prolonged skin contact.

**HYGIENE MEASURES**

DO NOT SMOKE IN WORK AREA! When using do not eat, drink or smoke. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE	Aerosol Liquid
COLOUR	Brown
ODOUR	Solvent.
SOLUBILITY	Soluble in Organic solvents.
VOLATILE ORGANIC COMPOUND (VOC)	507.5 g/litre

**10 STABILITY AND REACTIVITY****STABILITY**

Stable under normal temperature conditions and recommended use. Avoid: Heat, sparks, flames. Shocks and physical damage.

**CONDITIONS TO AVOID**

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

**MATERIALS TO AVOID**

Strong alkalis. Strong oxidising substances.

**HAZARDOUS DECOMPOSITION PRODUCTS**

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Nitrous gases (NO<sub>x</sub>).

**11 TOXICOLOGICAL INFORMATION****GENERAL INFORMATION**

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

**INHALATION**

High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.

**INGESTION**

May cause discomfort if swallowed.

**SKIN CONTACT**

May cause defatting of the skin, but is not an irritant.

**EYE CONTACT**

Spray and vapour in the eyes may cause irritation and smarting.

**HEALTH WARNINGS**

Because of quantity and composition, the health hazard is small.

**12 ECOLOGICAL INFORMATION****ECOTOXICITY**

No negative effects on the aquatic environment are known.

**13 DISPOSAL CONSIDERATIONS****GENERAL INFORMATION**

Do not puncture or incinerate even when empty. Empty aerosols should be recycled where facilities exist. Full or part full aerosols should be disposed of as hazardous waste in accordance with local authority requirements.

**DISPOSAL METHODS**

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements. Do not allow runoff to sewer, waterway or ground.

**14 TRANSPORT INFORMATION**

**(Aerosol) Mechoil**

UK ROAD CLASS	2.1		
PROPER SHIPPING NAME	AEROSOLS		
UN NO. ROAD	1950	UK ROAD PACK GR.	#
ADR CLASS NO.	2.1	ADR CLASS	Class 2: Gases
ADR PACK GROUP	#	ADR LABEL NO.	2.1
CEFIC TEC(R) NO.	20G5F	RID CLASS NO.	2.1
RID PACK GROUP	#	UN NO. SEA	1950
IMDG CLASS	2.1	IMDG PAGE NO.	93 (vol 2)
IMDG PACK GR.	#	EMS	F-D, S-U
MFAG	See Guide	MARINE POLLUTANT	No.
UN NO. AIR	1950	AIR CLASS	2.1
AIR PACK GR.	#		

### 15 REGULATORY INFORMATION

#### LABELLING



Extremely Flammable

#### RISK PHRASES

R12	Extremely flammable.
R66	Repeated exposure may cause skin dryness or cracking.

#### SAFETY PHRASES

S2	Keep out of the reach of children
S9	Keep container in a well-ventilated place.
S16	Keep away from sources of ignition - No smoking.
S23	Do not breathe vapour/spray.
S37	Wear suitable gloves.
S51	Use only in well-ventilated areas.
S35	This material and its container must be disposed of in a safe way.

#### STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

#### GUIDANCE NOTES

Workplace Exposure Limits EH40.

### 16 OTHER INFORMATION

#### GENERAL INFORMATION

This product has been manufactured under ISO 9001 and ISO 14001 Quality and Environmental Management Systems.

Only trained personnel should use this material.

REVISION DATE 05/06/2009

REV. NO./REPL. SDS GENERATED 4

**(Aerosol) Mechoil**

RISK PHRASES IN FULL

- |     |   |
|-----|---|
| R10 | Flammable.  |
| R12 | Extremely flammable.                                  |
| R65 | Harmful: may cause lung damage if swallowed.          |
| R66 | Repeated exposure may cause skin dryness or cracking. |

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.