



## SAFETY DATA SHEET (AEROSOL) SILICONE SPRAY ORANGE

### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME (AEROSOL) SILICONE SPRAY ORANGE  
 PRODUCT NO. A55  
 APPLICATION Dressing  
 SUPPLIER AUTOSMART  
 LYNN LANE  
 SHENSTONE  
 STAFFORDSHIRE  
 WS14 0DH  
 (+44) 01543 481616  
 (+44) 01543 481549  
 EMERGENCY TELEPHONE DGSA Helpline - (+44) 07808 971321  
 Tel:01543 481616/Fax: 01543 481549

### 2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
BUTANE	203-448-7	106-97-8	30-60%	F+;R12
HEXANE-norm	203-777-6	110-54-3	< 1%	F;R11 Repr3;R62 Xn;R65,R48/20 Xi;R38 R67 N;R51/53
PETROLEUM DISTILATE	203-777-6	64741-84-0	30-60%	Xn;R65. F;R11. N;R51/53.
PROPANE	200-827-9	74-98-6	10-30%	F+;R12

The Full Text for all R-Phrases are Displayed in Section 16

### 3 HAZARDS IDENTIFICATION

Extremely flammable. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION F+;R12. N;R51/53.

### 4 FIRST-AID MEASURES

#### INHALATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

#### INGESTION

DO NOT INDUCE VOMITING! Rinse mouth thoroughly. Drink plenty of water. Get medical attention if any discomfort continues.

#### SKIN CONTACT

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

#### EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

### 5 FIRE-FIGHTING MEASURES

#### EXTINGUISHING MEDIA

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

#### SPECIAL FIRE FIGHTING PROCEDURES

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours. Be aware of danger of explosion.

**(AEROSOL) SILICONE SPRAY ORANGE****UNUSUAL FIRE & EXPLOSION HAZARDS**

Aerosol cans may explode in a fire. **HIGHLY FLAMMABLE!**

**SPECIFIC HAZARDS**

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Nitrous gases (NO<sub>x</sub>).

**6 ACCIDENTAL RELEASE MEASURES****PERSONAL PRECAUTIONS**

For personal protection, see section 8.

**ENVIRONMENTAL PRECAUTIONS**

Do not discharge into drains, water courses or onto the ground.

**SPILL CLEAN UP METHODS**

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers.

**7 HANDLING AND STORAGE****USAGE PRECAUTIONS**

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Read and follow manufacturer's recommendations. During application and drying, solvent vapours will be emitted. Eliminate all sources of ignition.

**STORAGE PRECAUTIONS**

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. Keep away from heat, sparks and open flame. Store in tightly closed original container in a dry and cool place.

**8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Name	Std	LT - ppm	LT - mg/m <sup>3</sup>	ST - ppm	ST - mg/m <sup>3</sup>
BUTANE	WEL	600 ppm	1450 mg/m <sup>3</sup>	750 ppm	1810 mg/m <sup>3</sup>
HEXANE-norm	WEL	20 ppm	72 mg/m <sup>3</sup>		
PETROLEUM DISTILATE	WEL		1000 mg/m <sup>3</sup>		
PROPANE		Asphyxiating Asphyxiating	Asphyxiating	Asphyxiating Asphyxiating	Asphyxiating

**INGREDIENT COMMENTS**

WEL = Workplace Exposure Limits

**PROTECTIVE EQUIPMENT****PROCESS CONDITIONS**

Provide eyewash station.

**ENGINEERING MEASURES**

No specific ventilation requirements noted, except this product must not be used in a confined space without good ventilation.

**RESPIRATORY EQUIPMENT**

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Workplace Exposure Limit.

**HAND PROTECTION**

Use protective gloves made of: Polyvinyl chloride (PVC). The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

**EYE PROTECTION**

Wear approved, tight fitting safety glasses where splashing is probable.

**(AEROSOL) SILICONE SPRAY ORANGE****OTHER PROTECTION**

Wear appropriate clothing to prevent any possibility of skin contact.

**HYGIENE MEASURES**

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE	Aerosol Liquid
COLOUR	Clear
ODOUR	Pleasant, agreeable.
SOLUBILITY	Soluble in Organic solvents. Insoluble in water
VOLATILE ORGANIC COMPOUND (VOC)	585 g/litre

**10 STABILITY AND REACTIVITY****STABILITY**

Stable under normal temperature conditions. Avoid: Heat, sparks, flames. Shocks and physical damage.

**CONDITIONS TO AVOID**

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

**HAZARDOUS DECOMPOSITION PRODUCTS**

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Nitrous gases (NO<sub>x</sub>).

**11 TOXICOLOGICAL INFORMATION**

TOXIC DOSE 1 - LD 50 > 4000 mg/kg (oral rat)

**INHALATION**

High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.

**INGESTION**

May cause discomfort if swallowed. Drowsiness, dizziness, disorientation, vertigo.

**SKIN CONTACT**

May cause defatting of the skin, but is not an irritant.

**EYE CONTACT**

Spray and vapour in the eyes may cause irritation and smarting.

**HEALTH WARNINGS**

Because of limited volume in an aerosol, and that the contents can hardly be swallowed, risk of poisoning is regarded to be small.

**ROUTE OF ENTRY**

Inhalation. Ingestion.

**12 ECOLOGICAL INFORMATION****ECOTOXICITY**

Dangerous for the environment if discharged into watercourses.

**13 DISPOSAL CONSIDERATIONS****DISPOSAL METHODS**

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements. Do not allow runoff to sewer, waterway or ground.

**14 TRANSPORT INFORMATION**

**(AEROSOL) SILICONE SPRAY ORANGE**

PROPER SHIPPING NAME	AEROSOL, flammable		
UN NO. ROAD	1950	ADR CLASS NO.	2
ADR CLASS	Class 2.1: Flammable gases.	ADR PACK GROUP	5 (f)
UN NO. SEA	1950	IMDG CLASS	2
IMDG PAGE NO.	93 (vol 2)		

**15 REGULATORY INFORMATION**

## LABELLING



Extremely Flammable



Dangerous for the environment

## RISK PHRASES

R12	Extremely flammable.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## SAFETY PHRASES

S2	Keep out of the reach of children
S9	Keep container in a well-ventilated place.
S16	Keep away from sources of ignition - No smoking.
S23	Do not breathe vapour/spray.
S51	Use only in well-ventilated areas.
S60	This material and its container must be disposed of as hazardous waste.
S61	Avoid release to the environment. Refer to special instructions/safety data sheets.

## STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

## GUIDANCE NOTES

Workplace Exposure Limits EH40.

**16 OTHER INFORMATION**

## GENERAL INFORMATION

Only trained personnel should use this material.

REVISION DATE	04/03
REV. NO./REPL. SDS GENERATED	1 - 03/1999, 2(06/02)
SDS NO.	3

**(AEROSOL) SILICONE SPRAY ORANGE**

## RISK PHRASES IN FULL

R11	Highly flammable.
R12	Extremely flammable.
R38	Irritating to skin.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R62	Possible risk of impaired fertility.
R65	Harmful: may cause lung damage if swallowed.
R67	Vapours may cause drowsiness and dizziness.

## DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.