



## SAFETY DATA SHEET (Aerosol) White Grease

### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	(Aerosol) White Grease
SUPPLIER	Autosmart International Ltd Lynn Lane, Shenstone, nr Lichfield Staffordshire. WS14 0DH England www.autosmartinternational.com Tel: +44 (0) 1543 481616 (09:00 - 17:00) Fax: +44 (0) 1543 481549 (09:00 - 17:00) info@autosmartinternational.com
PRODUCT NO.	A59-6
APPLICATION	Lubricant
EMERGENCY TELEPHONE	Mob: +44 (0) 7808 971321 (24hrs) Tel: +44 (0) 1543 481616 (09:00 - 17:00) Fax: +44 (0) 1543 481549 (09:00 - 17:00)

### 2 HAZARDS IDENTIFICATION

Extremely flammable. Irritating to skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION (1999/45) Xi;R38. F+;R12. N;R51/53.

### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification (67/548)
BUTANE	203-448-7	106-97-8	10-30%	F+;R12
PROPANE	200-827-9	74-98-6	10-30%	F+;R12
SPECIAL BOILING POINT SPIRIT 60/95 (<3% n-HEXANE)	265-151-9	64742-49-0	30-60%	Xn;R65. Xi;R38. F;R11. N;R51/53.

The Full Text for all R-Phrases are Displayed in Section 16

### 4 FIRST-AID MEASURES

#### INHALATION

Move the exposed person to fresh air at once. Provide fresh air, warmth and rest, preferably in a comfortable upright sitting position. Get medical attention if any discomfort continues.

#### INGESTION

DO NOT INDUCE VOMITING! Rinse mouth thoroughly. Drink plenty of water. Get medical attention if any discomfort continues.

#### SKIN CONTACT

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

#### EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

### 5 FIRE-FIGHTING MEASURES

#### EXTINGUISHING MEDIA

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

#### SPECIAL FIRE FIGHTING PROCEDURES

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours. Be aware of danger of explosion.

**(Aerosol) White Grease****UNUSUAL FIRE & EXPLOSION HAZARDS**

Aerosol cans may explode in a fire. HIGHLY FLAMMABLE!

**SPECIFIC HAZARDS**

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Nitrous gases (NO<sub>x</sub>).

**6 ACCIDENTAL RELEASE MEASURES****PERSONAL PRECAUTIONS**

For personal protection, see section 8.

**ENVIRONMENTAL PRECAUTIONS**

Do not discharge into drains, water courses or onto the ground.

**SPILL CLEAN UP METHODS**

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers.

**7 HANDLING AND STORAGE****USAGE PRECAUTIONS**

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Read and follow manufacturer's recommendations. During application and drying, solvent vapours will be emitted. Eliminate all sources of ignition.

**STORAGE PRECAUTIONS**

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. Keep away from heat, sparks and open flame. Store in tightly closed original container in a dry and cool place.

**8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
BUTANE	WEL	600 ppm	1450 mg/m <sup>3</sup>	750 ppm	1810 mg/m <sup>3</sup>	
PROPANE		Asphyxiating Asphyxiating	Asphyxiating	Asphyxiating Asphyxiating	Asphyxiating	
SPECIAL BOILING POINT SPIRIT 60/95 (<3% n-HEXANE)	WEL		1000 mg/m <sup>3</sup>			

WEL = Workplace Exposure Limit.

**INGREDIENT COMMENTS**

WEL = Workplace Exposure Limits

**PROTECTIVE EQUIPMENT****ENGINEERING MEASURES**

No specific ventilation requirements noted, except this product must not be used in a confined space without good ventilation.

**RESPIRATORY EQUIPMENT**

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit.

**HAND PROTECTION**

Chemical resistant gloves required for prolonged or repeated contact. Use protective gloves made of: Polyvinyl chloride (PVC). The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

**EYE PROTECTION**

Wear splash-proof eye goggles to prevent any possibility of eye contact.

**OTHER PROTECTION**

Wear appropriate clothing to prevent any possibility of skin contact. Provide eyewash station.

**HYGIENE MEASURES**

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

**(Aerosol) White Grease**

APPEARANCE	Viscous Liquid Aerosol
COLOUR	White
ODOUR	Strong. Solvent.
SOLUBILITY	Insoluble in water Miscible with: Ordinary solvents.
VOLATILE ORGANIC COMPOUND (VOC)	452.5

**10 STABILITY AND REACTIVITY**

## STABILITY

Stable under normal temperature conditions. Avoid: Heat, sparks, flames. Shocks and physical damage.

## CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

## HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Nitrous gases (NO<sub>x</sub>).

**11 TOXICOLOGICAL INFORMATION**

## GENERAL INFORMATION

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

## INHALATION

High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.

## INGESTION

May cause discomfort if swallowed.

## SKIN CONTACT

May cause defatting of the skin, but is not an irritant.

## EYE CONTACT

No specific health warnings noted.

## HEALTH WARNINGS

Because of quantity and composition, the health hazard is small.

## ROUTE OF ENTRY

Inhalation. Ingestion.

**12 ECOLOGICAL INFORMATION**

## ECOTOXICITY

Dangerous for the environment if discharged into watercourses.

**13 DISPOSAL CONSIDERATIONS**

## GENERAL INFORMATION

Do not puncture or incinerate even when empty. Empty aerosols should be recycled where facilities exist. Full or part full aerosols should be disposed of as hazardous waste in accordance with local authority requirements.

## DISPOSAL METHODS

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements. Do not allow runoff to sewer, waterway or ground. Recover and reclaim or recycle, if practical.

**14 TRANSPORT INFORMATION**

UK ROAD CLASS	2.1	UK ROAD PACK GR.	#
PROPER SHIPPING NAME	AEROSOLS	ADR CLASS	Class 2.1: Flammable gases.
UN NO. ROAD	1950	ADR LABEL NO.	2.1
ADR CLASS NO.	2.1		
ADR PACK GROUP	#		

**(Aerosol) White Grease**

CEPIC TEC(R) NO.	20G5F	RID CLASS NO.	2.1
RID PACK GROUP	#	UN NO. SEA	1950
IMDG CLASS	2.1	IMDG PAGE NO.	2.1
IMDG PACK GR.	#	EMS	F-D, S-U
MARINE POLLUTANT	No.	UN NO. AIR	1950
AIR CLASS	2.1	AIR PACK GR.	#

**15 REGULATORY INFORMATION**

## LABELLING



Irritant



Extremely Flammable



Dangerous for the environment

## RISK PHRASES

R12	Extremely flammable.
R38	Irritating to skin.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## SAFETY PHRASES

S9	Keep container in a well-ventilated place.
S16	Keep away from sources of ignition - No smoking.
S23	Do not breathe vapour/spray.
S24	Avoid contact with skin.
S37	Wear suitable gloves.
S38	In case of insufficient ventilation, wear suitable respiratory equipment.
S57	Use appropriate containment to avoid environmental contamination.
S61	Avoid release to the environment. Refer to special instructions/safety data sheets.

## STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

## GUIDANCE NOTES

Workplace Exposure Limits EH40.

**16 OTHER INFORMATION**

## GENERAL INFORMATION

Only trained personnel should use this material. This product has been manufactured under ISO 9001 and ISO 14001 Quality and Environmental Management Systems.

REVISION DATE 17/03/2010

REV. NO./REPL. SDS GENERATED 2

## RISK PHRASES IN FULL

R12	Extremely flammable.
R65	Harmful: may cause lung damage if swallowed.
R11	Highly flammable.
R38	Irritating to skin.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.