



## SAFETY DATA SHEET (Aerosol) Blast Cool

### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	(Aerosol) Blast Cool
PRODUCT NO.	A217
APPLICATION	Air Freshener
SUPPLIER	Autosmart International Ltd Lynn Lane, Shenstone, nr Lichfield Staffordshire. WS14 0DH England www.autosmartinternational.com Tel: +44 (0) 1543 481616 (09:00 - 17:00) Fax: +44 (0) 1543 481549 (09:00 - 17:00) info@autosmartinternational.com
EMERGENCY TELEPHONE	Mob: +44 (0) 7808 971321 (24hrs) Tel: +44 (0) 1543 481616 (09:00 - 17:00) Fax: +44 (0) 1543 481549 (09:00 - 17:00)

### 2 HAZARDS IDENTIFICATION

Extremely flammable. Vapours may cause drowsiness and dizziness.

CLASSIFICATION F+;R12. R67.

### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
BUTANE	203-448-7	106-97-8	30-60%	F+;R12
PROPAN-2-OL	200-661-7	67-63-0	10-30%	F;R11 Xi;R36 R67
PROPANE	200-827-9	74-98-6	30-60%	F+;R12

The Full Text for all R-Phrases are Displayed in Section 16

### 4 FIRST-AID MEASURES

#### INHALATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

#### INGESTION

DO NOT INDUCE VOMITING! Rinse mouth thoroughly. Drink plenty of water. Get medical attention if any discomfort continues.

#### SKIN CONTACT

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

#### EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

### 5 FIRE-FIGHTING MEASURES

#### EXTINGUISHING MEDIA

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

#### SPECIAL FIRE FIGHTING PROCEDURES

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours. Be aware of danger of explosion.

**(Aerosol) Blast Cool****UNUSUAL FIRE & EXPLOSION HAZARDS**

Aerosol cans may explode in a fire. **HIGHLY FLAMMABLE!**

**SPECIFIC HAZARDS**

Aerosol containers can explode when heated, due to excessive pressure build-up. Fire creates: Carbon dioxide (CO<sub>2</sub>). Carbon monoxide (CO). Nitrous gases (NO<sub>x</sub>).

**6 ACCIDENTAL RELEASE MEASURES****PERSONAL PRECAUTIONS**

For personal protection, see section 8.

**ENVIRONMENTAL PRECAUTIONS**

Do not discharge into drains, water courses or onto the ground.

**SPILL CLEAN UP METHODS**

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers.

**7 HANDLING AND STORAGE****USAGE PRECAUTIONS**

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Read and follow manufacturer's recommendations. During application and drying, solvent vapours will be emitted. Eliminate all sources of ignition.

**STORAGE PRECAUTIONS**

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. Keep away from heat, sparks and open flame.

Pressurised container: Must not be exposed for temperatures above 50°C. Store in tightly closed original container in a dry and cool place.

**STORAGE CLASS**

Flammable compressed gas storage.

**8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Name	Std	LT - ppm	LT - mg/m <sup>3</sup>	ST - ppm	ST - mg/m <sup>3</sup>
BUTANE	WEL	600 ppm	1450 mg/m <sup>3</sup>	750 ppm	1810 mg/m <sup>3</sup>
PROPAN-2-OL	WEL	400 ppm	999 mg/m <sup>3</sup>	500 ppm	1250 mg/m <sup>3</sup>
PROPANE		Asphyxiating Asphyxiating	Asphyxiating	Asphyxiating Asphyxiating	Asphyxiating

**INGREDIENT COMMENTS**

WEL = Workplace Exposure Limits

**PROTECTIVE EQUIPMENT****PROCESS CONDITIONS**

Provide eyewash station.

**ENGINEERING MEASURES**

Observe Workplace Exposure Limits and minimise the risk of inhalation of vapours.

**RESPIRATORY EQUIPMENT**

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Workplace Exposure Limit.

**HAND PROTECTION**

Use protective gloves made of: Polyvinyl chloride (PVC). The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

**EYE PROTECTION**

Not relevant.

**OTHER PROTECTION**

Wear appropriate clothing to prevent repeated or prolonged skin contact.

## (Aerosol) Blast Cool

### HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! When using do not eat, drink or smoke. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Aerosol Clear liquid		
COLOUR	Colourless		
ODOUR	Characteristic		
RELATIVE DENSITY	1.000 (20°C)	VOLATILE ORGANIC COMPOUND (VOC)	568 g/litre

## 10 STABILITY AND REACTIVITY

### STABILITY

Stable under normal temperature conditions and recommended use. Avoid: Heat, sparks, flames. Shocks and physical damage.

### CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

### MATERIALS TO AVOID

Strong alkalis. Strong oxidising substances.

### HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Nitrous gases (NO<sub>x</sub>).

## 11 TOXICOLOGICAL INFORMATION

### INHALATION

Vapour may irritate respiratory system or lungs. Vapours may cause drowsiness and dizziness.

### INGESTION

Harmful: may cause lung damage if swallowed.

### SKIN CONTACT

May cause defatting of the skin, but is not an irritant.

### EYE CONTACT

Spray and vapour in the eyes may cause irritation and smarting.

### HEALTH WARNINGS

Because of quantity and composition, the health hazard is small.

## 12 ECOLOGICAL INFORMATION

### ECOTOXICITY

No negative effects on the aquatic environment are known.

## 13 DISPOSAL CONSIDERATIONS

### GENERAL INFORMATION

Do not puncture or incinerate even when empty. Empty aerosols should be recycled where facilities exist. Full or part full aerosols should be disposed of as hazardous waste in accordance with local authority requirements.

### DISPOSAL METHODS

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements. Do not allow runoff to sewer, waterway or ground.

## 14 TRANSPORT INFORMATION



UK ROAD CLASS

2.1

**(Aerosol) Blast Cool**

PROPER SHIPPING NAME		AEROSOLS	
UN NO. ROAD	1950	UK ROAD PACK GR.	#
ADR CLASS NO.	2.1	ADR CLASS	Class 2: Gases
ADR PACK GROUP	#	ADR LABEL NO.	2.1
CEFIC TEC(R) NO.	20G5F	RID CLASS NO.	2.1
RID PACK GROUP	#	UN NO. SEA	1950
IMDG CLASS	2.1	IMDG PAGE NO.	93 (vol 2)
IMDG PACK GR.	#	EMS	F-D, S-U
MARINE POLLUTANT	No.	UN NO. AIR	1950
AIR CLASS	2.1	AIR PACK GR.	#

**15 REGULATORY INFORMATION**

## LABELLING



Extremely Flammable

## RISK PHRASES

R12	Extremely flammable.
R67	Vapours may cause drowsiness and dizziness.

## SAFETY PHRASES

S9	Keep container in a well-ventilated place.
S16	Keep away from sources of ignition - No smoking.
S35	This material and its container must be disposed of in a safe way.
S51	Use only in well-ventilated areas.
S2	Keep out of the reach of children
S23	Do not breathe vapour/spray.

## UK REGULATORY REFERENCES

Health and Safety at Work Act 1974.

## STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations. Control of Substances Hazardous to Health.

**16 OTHER INFORMATION**

## GENERAL INFORMATION

Only trained personnel should use this material. This product has been manufactured under ISO 9001 and ISO 14001 Quality and Environmental Management Systems.

REVISION DATE 03/04/2008

REV. NO./REPL. SDS GENERATED 1

## RISK PHRASES IN FULL

R11	Highly flammable.
R12	Extremely flammable.
R36	Irritating to eyes.
R67	Vapours may cause drowsiness and dizziness.

## DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.