



SAFETY DATA SHEET (Aerosol) Silver Alloy

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME (Aerosol) Silver Alloy

SUPPLIER Autosmart International Ltd
Lynn Lane,
Shenstone, nr Lichfield
Staffordshire. WS14 0DH
England
www.autosmartinternational.com
Tel: +44 (0) 1543 481616 (09:00 - 17:00)
Fax: +44 (0) 1543 481549 (09:00 - 17:00)
info@autosmartinternational.com

PRODUCT NO. A50

APPLICATION Paint

EMERGENCY TELEPHONE Mob: +44 (0) 7808 971321 (24hrs)
Tel: +44 (0) 1543 481616 (09:00 - 17:00)
Fax: +44 (0) 1543 481549 (09:00 - 17:00)

2 HAZARDS IDENTIFICATION

Extremely flammable. Harmful by inhalation and in contact with skin. Repeated exposure may cause skin dryness or cracking. Irritating to eyes.

CLASSIFICATION (1999/45) Xn;R20/21. Xi;R36. F+;R12. R66.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification (67/548)
ACETONE	200-662-2	67-64-1	30-60%	F;R11 Xi;R36 R66 R67
BUTANE	203-448-7	106-97-8	10-30%	F+;R12
PROPANE	200-827-9	74-98-6	10-30%	F+;R12
XYLENE	215-535-7	1330-20-7	10-30%	R10 Xn;R20/21 Xi;R38

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INGESTION

DO NOT INDUCE VOMITING! Rinse mouth thoroughly. Drink plenty of water. Get medical attention if any discomfort continues.

SKIN CONTACT

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

(Aerosol) Silver Alloy**SPECIAL FIRE FIGHTING PROCEDURES**

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours. Be aware of danger of explosion.

UNUSUAL FIRE & EXPLOSION HAZARDS

Aerosol cans may explode in a fire. **HIGHLY FLAMMABLE!**

SPECIFIC HAZARDS

Aerosol containers can explode when heated, due to excessive pressure build-up. Fire creates: Carbon dioxide (CO₂). Carbon monoxide (CO). Nitrous gases (NO_x).

6 ACCIDENTAL RELEASE MEASURES**PERSONAL PRECAUTIONS**

For personal protection, see section 8.

ENVIRONMENTAL PRECAUTIONS

Do not discharge into drains, water courses or onto the ground.

SPILL CLEAN UP METHODS

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers.

7 HANDLING AND STORAGE**USAGE PRECAUTIONS**

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Read and follow manufacturer's recommendations. During application and drying, solvent vapours will be emitted. Eliminate all sources of ignition.

STORAGE PRECAUTIONS

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. Keep away from heat, sparks and open flame.
Pressurised container: Must not be exposed to temperatures above 50°C. Store in tightly closed original container in a dry and cool place.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
ACETONE	WEL	500 ppm	1210 mg/m ³	1500 ppm	3620 mg/m ³	
BUTANE	WEL	600 ppm	1450 mg/m ³	750 ppm	1810 mg/m ³	
PROPANE		Asphyxiating Asphyxiating	Asphyxiating	Asphyxiating Asphyxiating	Asphyxiating	
XYLENE	WEL	50 ppm	220 mg/m ³	100 ppm	441 mg/m ³	Sk

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through skin.

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT**PROCESS CONDITIONS**

Provide eyewash station.

ENGINEERING MEASURES

Observe occupational exposure limits and minimize the risk of inhalation of vapours. No specific ventilation requirements noted, except this product must not be used in a confined space without good ventilation.

RESPIRATORY EQUIPMENT

If ventilation is insufficient, suitable respiratory protection must be provided. Wear mask supplied with: Gas cartridge suitable for organic substances.

HAND PROTECTION

Use protective gloves made of: Butyl rubber. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

(Aerosol) Silver Alloy

EYE PROTECTION

Wear approved chemical safety goggles where eye exposure is reasonably probable.

OTHER PROTECTION

Wear appropriate clothing to prevent repeated or prolonged skin contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! When using do not eat, drink or smoke. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Aerosol Liquid
COLOUR	Silver
ODOUR	Acetone, ketone.
VOLATILE ORGANIC COMPOUND (VOC)	540

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions and recommended use. Avoid: Heat, sparks, flames. Shocks and physical damage.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

MATERIALS TO AVOID

Strong alkalis. Strong oxidising substances.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂). Nitrous gases (NO_x).

11 TOXICOLOGICAL INFORMATION

GENERAL INFORMATION

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

INHALATION

Harmful by inhalation. High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting. Vapours may cause drowsiness and dizziness.

INGESTION

May cause discomfort if swallowed.

SKIN CONTACT

Harmful in contact with skin.

EYE CONTACT

Irritating to eyes.

HEALTH WARNINGS

Because of quantity and composition, the health hazard is small.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

No negative effects on the aquatic environment are known.

13 DISPOSAL CONSIDERATIONS

GENERAL INFORMATION

Do not puncture or incinerate even when empty. Empty aerosols should be recycled where facilities exist. Full or part full aerosols should be disposed of as hazardous waste in accordance with local authority requirements.

DISPOSAL METHODS

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements. Do not allow runoff to sewer, waterway or ground.

14 TRANSPORT INFORMATION

(Aerosol) Silver Alloy

UK ROAD CLASS	2.1		
PROPER SHIPPING NAME	AEROSOLS		
UN NO. ROAD	1950	UK ROAD PACK GR.	#
ADR CLASS NO.	2.1	ADR CLASS	Class 2: Gases
ADR PACK GROUP	#	ADR LABEL NO.	2.1
CEFIC TEC(R) NO.	20G5F	RID CLASS NO.	2.1
RID PACK GROUP	#	UN NO. SEA	1950
IMDG CLASS	2.1	IMDG PAGE NO.	93 (vol 2)
IMDG PACK GR.	#	EMS	F-D, S-U
MFAG	See Guide	MARINE POLLUTANT	No.
UN NO. AIR	1950	AIR CLASS	2.1
AIR PACK GR.	#		

15 REGULATORY INFORMATION

LABELLING



Harmful



Extremely Flammable

CONTAINS

XYLENE

RISK PHRASES

R12	Extremely flammable.
R36	Irritating to eyes.
R20/21	Harmful by inhalation and in contact with skin.
R66	Repeated exposure may cause skin dryness or cracking.

SAFETY PHRASES

S9	Keep container in a well-ventilated place.
S16	Keep away from sources of ignition - No smoking.
S23	Do not breathe vapour/spray.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S36/37	Wear suitable protective clothing and gloves.
S38	In case of insufficient ventilation, wear suitable respiratory equipment.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

GUIDANCE NOTES

Workplace Exposure Limits EH40.

16 OTHER INFORMATION

GENERAL INFORMATION

Only trained personnel should use this material. This product has been manufactured under ISO 9001 and ISO 14001 Quality and Environmental Management Systems.

REVISION DATE 18/03/2010

REV. NO./REPL. SDS GENERATED 3

(Aerosol) Silver Alloy

RISK PHRASES IN FULL

R12	Extremely flammable.
R10	Flammable.
R20/21	Harmful by inhalation and in contact with skin.
R11	Highly flammable.
R36	Irritating to eyes.
R38	Irritating to skin.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.