



SAFETY DATA SHEET

All Purpose Wheel Cleaner

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	All Purpose Wheel Cleaner
PRODUCT NO.	777-11
APPLICATION	Wheel Cleaner
SUPPLIER	Autosmart International Ltd Lynn Lane, Shenstone, nr Lichfield Staffordshire. WS14 0DH England www.autosmartinternational.com Tel: +44 (0) 1543 481616 (09:00 - 17:00) Fax: +44 (0) 1543 481549 (09:00 - 17:00) info@autosmartinternational.com
EMERGENCY TELEPHONE	Mob: +44 (0) 7808 971321 (24hrs) Tel: +44 (0) 1543 481616 (09:00 - 17:00) Fax: +44 (0) 1543 481549 (09:00 - 17:00)

2 HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
2-BUTOXYETHANOL	203-905-0	111-76-2	< 1%	Xn;R20/21/22 Xi;R36/38
3-Lauramidopropyl trimethyl ammonium methyl sulfate	234-204-8	10595-49-0	< 1%	Xn;R22. Xi;R36. R43.
SODIUM HYDROXIDE	215-185-5	1310-73-2	< 1%	C;R35

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION

Get medical attention if any discomfort continues.

INGESTION

Rinse mouth thoroughly. Drink plenty of water. Get medical attention if any discomfort continues.

SKIN CONTACT

Remove contaminated clothing. Rinse with water. Use suitable lotion to moisturise skin. Get medical attention if any discomfort continues.

EYE CONTACT

Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Make sure to remove any contact lenses from the eyes before rinsing. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

SPECIFIC HAZARDS

Oxides of: Carbon. Nitrogen.

6 ACCIDENTAL RELEASE MEASURES

All Purpose Wheel Cleaner

PERSONAL PRECAUTIONS

For personal protection, see section 8.

ENVIRONMENTAL PRECAUTIONS

Do not discharge onto the ground or into water courses. To prevent release, place container with damaged side up.

SPILL CLEAN UP METHODS

Wear necessary protective equipment. Stop leak if possible without risk. Wash thoroughly after dealing with a spillage. Absorb in vermiculite, dry sand or earth and place into containers. Containers with collected spillage must be properly labelled with correct contents and hazard symbol. Flush area clean with lots of water. Be aware of potential for surfaces to become slippery. Flush to sewer if local regulations permit.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Read and follow manufacturer's recommendations. Avoid spilling, skin and eye contact.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
2-BUTOXYETHANOL	WEL	25 ppm		50 ppm		Sk
SODIUM HYDROXIDE	WEL				2 mg/m ³	

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through skin.

PROTECTIVE EQUIPMENT



PROCESS CONDITIONS

Provide eyewash station.

ENGINEERING MEASURES

No particular ventilation requirements.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Workplace Exposure Limit.

HAND PROTECTION

For prolonged or repeated skin contact use suitable protective gloves. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

EYE PROTECTION

Wear approved chemical safety goggles where eye exposure is reasonably probable.

OTHER PROTECTION

Wear appropriate clothing to prevent repeated or prolonged skin contact. Provide eyewash station.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid
COLOUR	Green
ODOUR	Pleasant, agreeable.
SOLUBILITY	Soluble in water
RELATIVE DENSITY	1.000 - 1.020 20

All Purpose Wheel Cleaner

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions and recommended use.

CONDITIONS TO AVOID

Avoid excessive heat for prolonged periods of time.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO₂).

11 TOXICOLOGICAL INFORMATION

INHALATION

No specific health warnings noted.

INGESTION

May cause discomfort if swallowed.

SKIN CONTACT

May cause defatting of the skin, but is not an irritant.

EYE CONTACT

Spray and vapour in the eyes may cause irritation and smarting.

HEALTH WARNINGS

Because of quantity and composition, the health hazard is small. Serious long-term effects are not known to be related to this type of product.

ROUTE OF ENTRY

Ingestion.

MEDICAL SYMPTOMS

No specific symptoms noted, but this chemical may still have adverse health impact, either in general or on certain individuals.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

No negative effects on the aquatic environment are known.

WATER HAZARD CLASSIFICATION

WGK 1

13 DISPOSAL CONSIDERATIONS

GENERAL INFORMATION

The packaging must be empty (drop-free, when inverted)

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements. Recover and reclaim or recycle, if practical.

14 TRANSPORT INFORMATION

GENERAL

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

ADR CLASS

Not dangerous according to ADR.

15 REGULATORY INFORMATION

RISK PHRASES

NC Not classified.

SAFETY PHRASES

S2 Keep out of the reach of children

S24/25 Avoid contact with skin and eyes.

P14 Contains 3-Lauramidopropyl trimethyl ammonium methyl sulfate. May produce an allergic reaction.

All Purpose Wheel Cleaner

DETERGENT LABELLING

< 5%

Non-ionic surfactants
Phosphates
Cationic surfactants
Perfumes

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

GUIDANCE NOTES

Workplace Exposure Limits EH40.

16 OTHER INFORMATION

GENERAL INFORMATION

Only trained personnel should use this material. This product has been manufactured under ISO 9001 and ISO 14001 Quality and Environmental Management Systems.

REVISION DATE 28/04/2009

REV. NO./REPL. SDS GENERATED 4

RISK PHRASES IN FULL

R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.
R22 Harmful if swallowed.
R35 Causes severe burns.
R36 Irritating to eyes.
R36/38 Irritating to eyes and skin.
R43 May cause sensitisation by skin contact.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.