



## SAFETY DATA SHEET CUT BACK

### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	CUT BACK
PRODUCT NO.	071
APPLICATION	Polish
SUPPLIER	Autosmart International Ltd Lynn Lane, Shenstone, nr Lichfield Staffordshire. WS14 0DH England www.autosmartinternational.com Tel: +44 (0) 1543 481616 (09:00 - 17:00) Fax: +44 (0) 1543 481549 (09:00 - 17:00) info@autosmartinternational.com
EMERGENCY TELEPHONE	Mob: +44 (0) 7808 971321 (24hrs) Tel: +44 (0) 1543 481616 (09:00 - 17:00) Fax: +44 (0) 1543 481549 (09:00 - 17:00)

### 2 HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
KEROSINE (PETROLEUM); STRAIGHT RUN KEROSINE	232-366-4	8008-20-6	10-30%	Xn;R65
N,N-dialkyl,dicocodimethylammoniumchloridesoluti on in alcohol		61789-77-3	1-5%	Xn;R22. C;R34. R10.
OLEYLBIS(2-HYDROXYETHYL)AMINE	246-807-3	25307-17-9	1-5%	Xn;R22. C;R34. N;R50.

The Full Text for all R-Phrases are Displayed in Section 16

### 4 FIRST-AID MEASURES

#### INHALATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

#### INGESTION

DO NOT INDUCE VOMITING! Rinse mouth thoroughly. Drink plenty of water. Get medical attention immediately! If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

#### SKIN CONTACT

Wash skin with soap and water. Get medical attention if any discomfort continues.

#### EYE CONTACT

Rinse the eye with water immediately. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

### 5 FIRE-FIGHTING MEASURES

#### EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

#### SPECIFIC HAZARDS

Oxides of: Carbon.

### 6 ACCIDENTAL RELEASE MEASURES

**CUT BACK****PERSONAL PRECAUTIONS**

For personal protection, see section 8.

**ENVIRONMENTAL PRECAUTIONS**

Do not discharge into drains, water courses or onto the ground.

**SPILL CLEAN UP METHODS**

Do not contaminate water sources or sewer. Collect spillage in containers, seal securely and deliver for disposal according to local regulations. Flush area clean with lots of water. Be aware of potential for surfaces to become slippery.

**7 HANDLING AND STORAGE****USAGE PRECAUTIONS**

Avoid spilling, skin and eye contact. Avoid inhalation of vapours. During application and drying, solvent vapours will be emitted.

**STORAGE PRECAUTIONS**

Store in tightly closed original container in a dry, cool and well-ventilated place.

**8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
KEROSINE (PETROLEUM); STRAIGHT RUN KEROSINE	WEL		800 mg/m3		

**INGREDIENT COMMENTS**

WEL = Workplace Exposure Limits

**PROTECTIVE EQUIPMENT****PROCESS CONDITIONS**

Provide eyewash station.

**ENGINEERING MEASURES**

No specific ventilation requirements noted, except this product must not be used in a confined space without good ventilation.

**RESPIRATORY EQUIPMENT**

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Workplace Exposure Limit.

**HAND PROTECTION**

Use protective gloves made of: Neoprene. Polyvinyl chloride (PVC). The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

**EYE PROTECTION**

No specific eye protection noted, but may be required anyway.

**OTHER PROTECTION**

Provide eyewash station. Wear appropriate clothing to prevent repeated or prolonged skin contact.

**HYGIENE MEASURES**

**DO NOT SMOKE IN WORK AREA!** Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE	Viscous Liquid		
COLOUR	Light brown		
ODOUR	Mild		
SOLUBILITY	Insoluble in water Miscible with Hydrocarbons.		
RELATIVE DENSITY	ca 1.175 (20°C)	FLASH POINT (°C)	> 62 CC (Closed cup).

**10 STABILITY AND REACTIVITY**

**CUT BACK****STABILITY**

Stable under normal temperature conditions and recommended use.

**CONDITIONS TO AVOID**

Avoid excessive heat for prolonged periods of time.

**HAZARDOUS DECOMPOSITION PRODUCTS**

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

**11 TOXICOLOGICAL INFORMATION**

TOXIC DOSE 1 - LD 50 > 4000 mg/kg (oral rat)

**GENERAL INFORMATION**

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

**INHALATION**

Vapours may cause headache, fatigue, dizziness and nausea.

**INGESTION**

May cause discomfort if swallowed.

**SKIN CONTACT**

May cause defatting of the skin, but is not an irritant.

**EYE CONTACT**

No specific health warnings noted.

**HEALTH WARNINGS**

Serious long-term effects are not known to be related to this type of product.

No specific acute or chronic health impact noted, but this chemical may still have adverse impact on human health, either in general or on certain individuals with pre-existing or latent health problems.

**ROUTE OF ENTRY**

Ingestion. Inhalation.

**MEDICAL SYMPTOMS**

No specific symptoms noted, but this chemical may still have adverse health impact, either in general or on certain individuals.

**12 ECOLOGICAL INFORMATION****ECOTOXICITY**

The product contains a substance which is toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

**OLEYBIS (2-HYDROXYETHYL) AMINE**

Cas No 25307-17-9/R50

LC50 0.39mg/L

EC50 <1mg/L

**13 DISPOSAL CONSIDERATIONS****DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements. Do not allow runoff to sewer, waterway or ground.

**14 TRANSPORT INFORMATION**

GENERAL	The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).		
UN NO. ROAD	0	ADR CLASS	Not dangerous according to ADR.

**15 REGULATORY INFORMATION****RISK PHRASES**

NC Not classified.

**SAFETY PHRASES**

S23 Do not breathe vapour/spray.

S37 Wear suitable gloves.

**CUT BACK**

S51 Use only in well-ventilated areas.  
P13 Safety data sheet available for professional user on request.

## STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

## GUIDANCE NOTES

Workplace Exposure Limits EH40.

**16 OTHER INFORMATION**

## GENERAL INFORMATION

Only trained personnel should use this material.

REVISION DATE 25/09/2007

REV. NO./REPL. SDS GENERATED 1

## RISK PHRASES IN FULL

R10 Flammable.  
R22 Harmful if swallowed.  
R34 Causes burns.  
R50 Very toxic to aquatic organisms.  
R65 Harmful: may cause lung damage if swallowed.

## DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.