



SAFETY DATA SHEET
LUXURY WAX POLISH

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME	LUXURY WAX POLISH
PRODUCT NO.	140
APPLICATION	Polish
SUPPLIER	AUTOSMART LYNN LANE SHENSTONE STAFFORDSHIRE WS14 0DH (+44) 01543 481616 (+44) 01543 481549
EMERGENCY TELEPHONE	DGSA Helpline - (+44) 07808 971321 Tel:01543 481616/Fax: 01543 481549

2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
N,N-dialkyl,dicocodimethylammoniumchloridesolution in alcohol)		61789-77-3	< 1%	Xn;R22. C;R34. R10.
OLEYLBIS(2-HYDROXYETHYL)AMINE	246-807-3	25307-17-9	< 1%	Xn;R22. C;R34. N;R50.
WHITE SPIRIT	265-185-4	64742-48-9	10-30%	Xn;R65. R10,R66.

The Full Text for all R-Phrases are Displayed in Section 16

3 HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INGESTION

DO NOT INDUCE VOMITING! Rinse mouth thoroughly. Drink plenty of water. Get medical attention immediately! If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

SKIN CONTACT

Wash skin with soap and water. Use suitable lotion to moisturise skin. Get medical attention if any discomfort continues.

EYE CONTACT

Rinse the eye with water immediately. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

SPECIFIC HAZARDS

Oxides of: Carbon.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

For personal protection, see section 8.

ENVIRONMENTAL PRECAUTIONS

Do not discharge into drains, water courses or onto the ground.

LUXURY WAX POLISH**SPILL CLEAN UP METHODS**

Do not contaminate water sources or sewer. Collect spillage in containers, seal securely and deliver for disposal according to local regulations. Flush area clean with lots of water. Be aware of potential for surfaces to become slippery.

7 HANDLING AND STORAGE**USAGE PRECAUTIONS**

Avoid spilling, skin and eye contact. Avoid inhalation of vapours. During application and drying, solvent vapours will be emitted.

STORAGE PRECAUTIONS

Store in tightly closed original container in a cool, dry well-ventilated place.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
WHITE SPIRIT	OES		1000 mg/m3		

INGREDIENT COMMENTS

OES = Occupational Exposure Standard.

PROTECTIVE EQUIPMENT**PROCESS CONDITIONS**

Provide eyewash station.

ENGINEERING MEASURES

No specific ventilation requirements noted, except this product must not be used in a confined space without good ventilation.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Occupational Exposure Limit. In case of inadequate ventilation or risk of inhalation of vapours, use suitable respiratory equipment with combination filter (type A2/P2).

HAND PROTECTION

Chemical resistant gloves required for prolonged or repeated contact. Use protective gloves made of: Nitrile. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

EYE PROTECTION

If risk of splashing, wear safety goggles or face shield.

OTHER PROTECTION

Provide eyewash station.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Viscous Liquid		
COLOUR	Yellow		
ODOUR	Pleasant, agreeable.		
SOLUBILITY	Insoluble in water Miscible with Hydrocarbons.		
RELATIVE DENSITY	ca 0.965 20	VISCOSITY	> 30 sec in a 3 mm ISO cup
FLASH POINT (°C)	> 62 CC (Closed cup).		

10 STABILITY AND REACTIVITY**STABILITY**

Stable under normal temperature conditions and recommended use.

CONDITIONS TO AVOID

Avoid excessive heat for prolonged periods of time.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO₂).

11 TOXICOLOGICAL INFORMATION

REVISION DATE: 04/03

LUXURY WAX POLISH

TOXIC DOSE 1 - LD 50 > 4000 mg/kg (oral rat)

GENERAL INFORMATION

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

INHALATION

Vapours may cause headache, fatigue, dizziness and nausea.

INGESTION

May cause discomfort if swallowed.

SKIN CONTACT

May cause defatting of the skin, but is not an irritant.

EYE CONTACT

No specific health warnings noted.

HEALTH WARNINGS

This product has low toxicity. Only large volumes may have adverse impact on human health.

ROUTE OF ENTRY

Ingestion. Inhalation.

MEDICAL SYMPTOMS

No specific symptoms noted, but this chemical may still have adverse health impact, either in general or on certain individuals.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

The product contains a substance which is toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

OLEYBIS (2-HYDROXYETHYL) AMINE

Cas No 25307-17-9/R50

LC50 0.39mg/L

EC50 <1mg/L

LC 50, 96 Hrs, FISH mg/l >100

EC 50, 48 Hrs, DAPHNIA, mg/l >100

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements. Do not allow runoff to sewer, waterway or ground.

14 TRANSPORT INFORMATION

GENERAL	The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).		
UN NO. ROAD	0	ADR CLASS	Not dangerous according to ADR.

15 REGULATORY INFORMATION

RISK PHRASES

NC Not classified.

SAFETY PHRASES

P13 Safety data sheet available for professional user on request.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

GUIDANCE NOTES

Occupational Exposure Limits EH40.

16 OTHER INFORMATION

GENERAL INFORMATION

Only trained personnel should use this material.

REVISION DATE 04/03

REV. NO./REPL. SDS GENERATED 1(03/99), 2(07/02)

SDS NO. 3

LUXURY WAX POLISH

RISK PHRASES IN FULL

R10	Flammable.
R22	Harmful if swallowed.
R34	Causes burns.
R50	Very toxic to aquatic organisms.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.