



SAFETY DATA SHEET

Liquid Wax

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	Liquid Wax
APPLICATION	Rinse aid
SUPPLIER	Autosmart International Ltd Lynn Lane, Shenstone, nr Lichfield Staffordshire. WS14 0DH England www.autosmartinternational.com Tel: +44 (0) 1543 481616 (09:00 - 17:00) Fax: +44 (0) 1543 481549 (09:00 - 17:00) info@autosmartinternational.com
EMERGENCY TELEPHONE	Mob: +44 (0) 7808 971321 (24hrs) Tel: +44 (0) 1543 481616 (09:00 - 17:00) Fax: +44 (0) 1543 481549 (09:00 - 17:00)

2 HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
PROPAN-2-OL	200-661-7	67-63-0	< 1%	F;R11 Xi;R36 R67

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION

Get medical attention if any discomfort continues.

INGESTION

DO NOT INDUCE VOMITING! Rinse mouth thoroughly. Drink plenty of water. Get medical attention if any discomfort continues.

SKIN CONTACT

Remove contaminated clothing. Rinse with water. Use suitable lotion to moisturise skin. Get medical attention if any discomfort continues.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

SPECIFIC HAZARDS

Oxides of: Carbon. Nitrogen.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

For personal protection, see section 8.

Liquid Wax

ENVIRONMENTAL PRECAUTIONS

Do not discharge onto the ground or into water courses. To prevent release, place container with damaged side up.

SPILL CLEAN UP METHODS

Wear necessary protective equipment. Stop leak if possible without risk. Wash thoroughly after dealing with a spillage. Large Spillages Absorb in vermiculite, dry sand or earth and place into containers. Flush area clean with lots of water. Be aware of potential for surfaces to become slippery. Do not contaminate water sources or sewer. Small quantities may be flushed to drains with plenty of water. Flush to sewer if local regulations permit.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Read and follow manufacturer's recommendations. Avoid spilling, skin and eye contact.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
PROPAN-2-OL	WEL	400 ppm	999 mg/m ³	500 ppm	1250 mg/m ³	

WEL = Workplace Exposure Limit.

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT



PROCESS CONDITIONS

Provide eyewash station.

ENGINEERING MEASURES

No particular ventilation requirements.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Workplace Exposure Limit.

HAND PROTECTION

Use protective gloves made of: Rubber (natural, latex). The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

EYE PROTECTION

Wear approved chemical safety goggles where eye exposure is reasonably probable.

OTHER PROTECTION

Provide eyewash station.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid		
COLOUR	Blue green		
ODOUR	Sweetish		
SOLUBILITY	Soluble in water Miscible with water.		
RELATIVE DENSITY	~ 1.000 (20°C)	pH-VALUE, CONC. SOLUTION	~ 8.0
VOLATILE ORGANIC COMPOUND (VOC)	2 g/litre		

Liquid Wax

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions and recommended use.

CONDITIONS TO AVOID

Avoid excessive heat for prolonged periods of time.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO₂).

11 TOXICOLOGICAL INFORMATION

TOXIC DOSE 1 - LD 50 > 4000 mg/kg (oral rat)

GENERAL INFORMATION

This product has low toxicity. Only large volumes may have adverse impact on human health.

INHALATION

No specific health warnings noted.

INGESTION

May cause discomfort if swallowed.

SKIN CONTACT

May cause defatting of the skin, but is not an irritant.

EYE CONTACT

Spray and vapour in the eyes may cause irritation and smarting.

HEALTH WARNINGS

Because of quantity and composition, the health hazard is small. Serious long-term effects are not known to be related to this type of product.

OTHER HEALTH EFFECTS

This substance has no evidence of carcinogenic properties.

ROUTE OF ENTRY

Ingestion. Skin and/or eye contact.

MEDICAL SYMPTOMS

No specific symptoms noted, but this chemical may still have adverse health impact, either in general or on certain individuals.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

No negative effects on the aquatic environment are known.

DEGRADABILITY

The product is expected to be biodegradable.

WATER HAZARD CLASSIFICATION

WGK 1

13 DISPOSAL CONSIDERATIONS

GENERAL INFORMATION

The packaging must be empty (drop-free, when inverted)

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements. Recover and reclaim or recycle, if practical.

14 TRANSPORT INFORMATION

GENERAL

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

No transport warning sign required.

15 REGULATORY INFORMATION

Liquid Wax

RISK PHRASES

NC Not classified.

SAFETY PHRASES

P13 Safety data sheet available for professional user on request.

S24/25 Avoid contact with skin and eyes.

EU DIRECTIVES

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

GUIDANCE NOTES

Workplace Exposure Limits EH40.

NATIONAL REGULATIONS

Commission Decision 2000/532/EC as amended by Decision 2001/118/EC establishing a list of wastes and hazardous waste pursuant to Council Directive 75/442/EEC on waste and Directive 91/689/EEC on hazardous waste with amendments.

16 OTHER INFORMATION

GENERAL INFORMATION

Only trained personnel should use this material.

REVISION DATE 06/10/2009

REV. NO./REPL. SDS GENERATED 1

RISK PHRASES IN FULL

R11 Highly flammable.

R36 Irritating to eyes.

R67 Vapours may cause drowsiness and dizziness.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.